



Harby 3-drawer wide chest
1HYC-300
23.2H | 30W | 17.7D (in)



Harby 4-drawer wide chest
1HYC-400
29.1H | 30W | 17.7D (in)

KEY FEATURES

- 1in thick tops and 0.71in base and sides and a 0.71in drawer bottom results in a very robust drawer
- Strength and stability tested to contract levels
- Optional locks to drawers
- Durable metal drawer runners
- Optional 0.5in CLEAN-TEC Solid-Surface top

MATERIAL/FABRICATION

Harby's carcass is made from a combination of 1in melamine-faced particle board and vinyl-wrapped medium density fiberboard. Double thickness drawer fronts with 0.71in back and sides and 0.71in drawer bottoms result in a very robust drawer. Corners are smooth for additional safety as well all edges being lipped in tough 2mm PVC.

CLEAN-TEC* is a solid, water-resistant material with a tactile feel and a seamless smooth finish. Highly resistant to bacteria and mold, CLEAN-TEC's non-porous nature makes it ideal for stringent infection-control practices and its low VOC (volatile organic compounds) minimize harmful emissions while supporting indoor air quality.

OPTIONS

- Locks to doors and drawers
- Other styles available in the range (see below)
- Optional 0.5in CLEAN-TEC* Solid-Surface top, these tops are available in white only, and are recommended for low-risk areas (as below)

COLOR/FINISH

Available in Natural Rockford Hickory finish. Optional CLEAN-TEC top is available in white only.

Optional CLEAN-TEC Top
6HYC-300-WH
Top Dims: 0.5H | 30W | 17.7D (in)
(Top not sold separately)



TEST STANDARDS

- Surface durability tested to BS6250
- Strength and stability tested to BS EN 4875 Part 7 Level 5 2006
- BS 476: Part 7: 1997 (Classification of the surface spread of flame of products)
- UL723 (Surface burning test - US standard)

INSTALLATION/FITTING

WARNING – PROFESSIONAL INSTALLATION REQUIRED.

This product is designed as permanently fixed institutional furniture and must be secured to the building structure prior to use. Not intended for freestanding or residential use.

The product requires professional installation and must be permanently secured to the building structure by a competent installer before use.

MAINTENANCE

Visit our care guidance section on our website for more information.

WARRANTY

7 year guarantee.