



SATRA Technology Centre Ltd
 Wyndham Way, Telford Way, Kettering,
 Northamptonshire, NN16 8SD United Kingdom
 Tel: +44 (0) 1536 410000
 email: info@satra.com
 www.satra.com



TECHNICAL REPORT

Pineapple Contracts Westmead Aylesford Maidstone Kent ME20 6XJ United Kingdom	SATRA reference:	FUR2007165	
		2424	1
	Report ID/Issue number:	41726/1	
	Your reference:	LLNPD07062024	
	Date samples received:	10/06/2024	
	Date(s) work carried out:	10/06/2024 to 09/07/2024	
	Date of report:	10/07/2024	

Testing Requirements

Testing of a table, described by the customer as the 'Ryno Pedestal Table' to EN 15372:2016 Test Level 3.

For SATRA's full terms and conditions see our website: <https://new.satra.com/satra-terms-and-conditions/>

For SATRA's statements regarding the confidentiality, publication and dissemination of this report, decision rules and UKAS accreditation please see the final page of this technical report.

Report Signed by:

Johnny Worthington


 Report Signatory

ASSESSMENT OF THE RYNO PEDESTAL TABLE

As requested by Pineapple Contracts, SATRA have assessed the table submitted as detailed below.

SAMPLE SUBMITTED

Sample reference: Ryno Pedestal Table
Testing conducted by: M Evans

**TESTS CARRIED OUT**

EN 15372:2016 – Test Level 3 – Furniture –Strength, durability and safety – Requirements for non-domestic tables.

The test methods used in clause 5.4 are described in EN 1730:2012.

CONCLUSION

The 'Ryno Pedestal Table' supplied for testing by Pineapple Contracts, has satisfied the relevant requirements of EN 15372:2016 – Test Level 3 – Furniture –Strength, durability and safety – Requirements for non-domestic tables, except for Clause 6, "Information for use".

RESULTS

RYNO PEDESTAL TABLE

EN 15372:2016 (Test Level 3)

Clause	Test Description	Result
5	Safety Requirements	
5.1	General	
	Edges of top directly in contact with user must be rounded or chamfered	Pass
	All other accessible edges shall be free from burrs or sharp edges	Pass
	Ends of hollow components are closed or capped	N/A
	Moveable and adjustable parts designed to avoid injuries	N/A
	Shall not be possible for load bearing parts to come loose unintentionally	Pass
	Parts that are lubricated should be protected from user	N/A
5.2	Shear and Squeeze Points	
5.2.1	Shear and squeeze points when setting up and folding	N/A
5.2.2	Shear and squeeze points under influence of powered mechanisms	N/A
5.2.3	Shear and squeeze points during use	Pass
5.3	Stability	
5.3.1.2	Tests for tables that are 950 mm in height or less	Pass
5.3.1.3	Tests for tables that are greater than 950 mm	N/A
5.3.2	Stability for tables with extension elements	N/A

EN 15372:2016 (Test Level 3) Continued

Clause	Test Description	Result
5.4	Strength and Durability	
EN 1730, 6.2	Horizontal Static Load for tables more than 600mm high and surface of $\geq 0.3\text{m}^2$ – Longitudinal	Pass
	Horizontal Static Load for tables more than 600mm high and surface of $\geq 0.3\text{m}^2$ – Transverse	Pass
	Horizontal Static Load for all other tables - Longitudinal	N/A
	Horizontal Static Load for all other tables - Transverse	N/A
EN 1730, 6.3.1	Vertical static load on main surface	Pass
EN 1730, 6.3.2	Additional static load where the main surface is $\geq 1600\text{mm}$ long	N/A
EN 1730, 6.3.3	Vertical static load on the ancillary surface	N/A
EN 1730 6.4.1 & 6.4.2	Horizontal durability Position Longitudinal	Pass
	Horizontal durability Position Transverse	Pass
EN 1730, 6.5	Vertical durability (where applicable)	Pass
EN 1730, 6.6.1 & 6.6.2	Vertical impact for tables with glass in their construction (Safety Glass)	N/A
	Vertical impact for tables with glass in their construction (Other Glass)	N/A
EN 1730, 6.6.1 & 6.6.3	Vertical impact for all other tables	Pass
EN 1730 6.9	Drop test for tables weighing more than 20 Kg – tables without glass	Pass
EN 1730 6.9	Drop test for tables weighing more than 20 Kg – tables with glass	N/A
EN 1730 7.2	Stability under vertical load (Main Surface)	Pass
	Stability under vertical load (Ancillary Surface)	N/A
EN 1730 7.3	Stability for tables with extension elements (drawers)	N/A
6	Information for use	N/T (see Note 1)

N/A denotes clause 'Not Applicable'.

N/T denotes clause 'Not Tested'.

COMMENTS

Note 1: No "Information for use" was supplied, and so the table was not assessed against the requirements of this clause.



Picture 1: Front view of the 'Ryno Pedestal Table'

Conditions of Use

Confidentiality and Dissemination

SATRA test reports may be forwarded to other parties if they are not changed in any way and are not marked as confidential. Test reports must not be published, for example by including it in advertisements, without the prior, written permission of SATRA.

Liability

Results given in this report refer only to the samples submitted for analysis and tested by SATRA. Comments are for guidance only.

A satisfactory test report in no way implies that the product tested is approved by SATRA and no warranty is given as to the performance of the product tested. SATRA shall not be liable for any subsequent loss or damage incurred by the client as a result of information supplied in the report.

Accreditation

Where the UKAS logo is included on the test report then tests marked ≠ fall outside the UKAS Accreditation Schedule for SATRA. Where no UKAS logo is included on the test report then none of the tests reported are covered by SATRA's UKAS Accreditation.

Tests marked ¥ are performed under SATRA's Flexible UKAS Schedule.

Opinions and interpretations fall outside the UKAS Accreditation for SATRA.

Uncertainty of Measurement and Decision Rules

Where values for uncertainty of measurement are included within the report then the uncertainty of the corresponding results are based on a standard uncertainty multiplied by a coverage factor $k=2$, which provides a coverage probability of approximately 95%.

When reporting results against a conformance statement (Pass/Fail or the allocation of a class or level) then uncertainty of measurement is taken into account based on a non-binary acceptance which itself is based on the guard band being equal to the expanded uncertainty.

Where the result corrected for uncertainty falls within the tolerance of the conformance statement then the risk of the conformance statement being a false accept or false reject is up to 2.5% and SATRA will in this instance quote a Pass/Fail, class, or level.

Where the result corrected for uncertainty falls outside of the tolerance of the conformance statement then the risk of the conformance statement being a false accept or false reject is up to 50%. In this instance SATRA will not provide a Pass/Fail statement or a class or level but will include information in the notes in relation to the result obtained.

SATRA's guidelines provide recommendations that are based upon SATRA's knowledge and experience. The guidelines are intended to indicate conformance by providing information on the likely performance or characteristics of a property. As such, uncertainty of measurement is not applied when evaluating results against guideline recommendations.
