



UK Registered Design No. 6195591 / 6195592



## KEY FEATURES

- One-piece design makes products water-resistant and prevents concealment of contraband
- Reduced-ligature design features
- Floor and wall securable with security fixings
- Sloping shelves reduce ability to climb
- Polyethylene material is 100% recyclable
- 100% waterproof construction with hygienic wipe-clean surface
- Available with a durable and hygienic solid grade laminate door recommended for use in low-medium risk environments

## MATERIAL/FABRICATION

Rotationally molded, durable polyethylene, one-piece construction provides excellent strength and stability. Flamed, textured finish further strengthens the fire-retardant, water-resistant, UV-stabilized shell. Anti-microbial material gives high chemical resistance (e.g. ammonia, sodium hydroxide) throughout the product. Item is fully recyclable as polyethylene can be melted down to create a whole new product.

Our Ryno Open Wardrobe has been designed to be the same depth and width as Ryno Chest and Ryno Desk.

## DOOR MATERIAL/FABRICATION

The Ryno wardrobe with door is specifically designed to provide secure storage in low to medium risk environments, with a strong emphasis on durability and safety.

It features a warm dark-gray Solid Grade Laminate (SGL) door that is water-resistant, robust, and hygienic. The door is securely fitted using a rust-resistant stainless steel piano hinge and anti-tamper security fixings. The unit is supplied fully assembled and is not suitable for retrofitting to existing models.

Available with either left-hand or right-hand hinge options, the wardrobe includes a single barrel lock, keyed-to-differ with up to 50 variations.

For further details on the door option, please refer to our safety notice and disclaimer on the next page.

## TEST STANDARDS

- Tested to ANSI/BIFMA X5.5:2012 standards
- Fire retardant to BS 5852:2006 ignition source 5, CAL 133, UL 94 HB and DIN 66084
- Tested to BS EN 16121:2013+A1:2017 Test Level 2 Severe
- UV resistance tested to UV 21+ stating it can withstand 21,000 sunlight hours
- Antibacterial Activity MOD iso 11196:2011
- Ryno ISO 11925 (2020)
- BS EN 16121:2023 Test Level 2 (SGL Door Testing)

## COLOR/FINISH

CORE COLORS



\* Please note: Ryno wardrobe with door is not available in OceanGreen

## OPTIONS



Ryno Open Wardrobe (fully shelved)  
1RYOW-00  
78.7H | 27.5W | 20.1D (in)  
Weight: 99lbs

Ryno Open Wardrobe (fully shelved)  
with door  
Right-hand door: 1RYWS-RH  
Left-hand door: 1RYWS-LH



Ryno Open Wardrobe (hanging)  
1RYOWH-00  
78.7H | 27.5W | 20.1D (in)  
Weight: 99lbs

Ryno Open Wardrobe (hanging) with  
door  
Right-hand door: 1RYWH-RH  
Left-hand door: 1RYWH-LH

Door Dims: 67.5H | 22.4W | 0.5 (in)



## ASSEMBLY

Arrives assembled and ready to use. All products must be secured to the wall and not be freestanding to avoid risk of injury

## MAINTENANCE

Avoid using abrasive materials or cleaning agents, solvents, steam cleaning or jet washing. Use bleach and chlorine disinfectant with caution and avoid placing in close proximity to sources of heat.

## INSTALLATION/FITTING

**WARNING – PROFESSIONAL INSTALLATION REQUIRED.**

This product is designed as permanently fixed institutional furniture and must be secured to the building structure prior to use. Not intended for freestanding or residential use.

The product requires professional installation and must be permanently secured to the building structure by a competent installer before use.

**Please note:** door option cannot be sold separately and retrofitted onto pre-existing products

## WARRANTY

We offer a **lifetime guarantee** on the Ryno wardrobe against all manufacturing faults, and a **5-year guarantee** on the solid-grade laminate door

## SAFETY NOTICE

When selecting the door option for the Ryno wardrobe, please be aware that it introduces additional safety considerations. The inclusion of a door may present potential ligature or entrapment risks. To ensure the highest level of safety, the wardrobe must be securely fixed to walls or floors using heavy-duty, anti-tamper fixings

This product is recommended for use in low-medium risk areas only, where the risk of self-harm or misuse is minimal. It is the responsibility of the installer and facility to determine the product's suitability for the intended environment and to carry out all necessary risk assessments prior to installation

If you have any questions or need further guidance, please contact our team

## DISCLAIMER

Extreme temperature changes (e.g. a cold night followed by a warm sunny day) may cause air inside the product to expand, causing short-term changes to its shape

Due to the nature of the rotational molding process, flat surfaces on Ryno® products may feature slight undulations which do not detract from the product's strength or durability

SGL door is not suitable for outdoor use